

Technical Specifications

	SVT-3PRO	SVT-4PRO
Output Power Rating	275W RMS @ 8 Ω 5% THD 450W RMS @ 4 Ω 5% THD	Mono-Bridged:900W RMS @ 8 Ω (3% THD) Mono-Bridged 1200W RMS @ 4 Ω (3% THD) 2x600W RMS @ 2 Ω (3% THD) 2x490W RMS @ 4 Ω (3% THD) 2x300W RMS @ 8 Ω (3% THD)
Maximum Gain	63dB	68dB Bridged Output
Tube Complement	12AX7 (4) 12AU7 (1)	12AX7 (3)
Power Requirements	~100-120 VAC, 50-60 Hz, 390W ~200-240 VAC, 50-60 Hz, 390W	~100-120 VAC, 50-60 Hz, 1.4 kVA, 1.4 kW ~200-240 VAC, 50-60 Hz, 1.4 kVA, 1.4 kW
Size (H x W x D)	4.0 x 19.0 x 17.4 in 102 x 442 x 394 mm	5.6 x 19.0 x 17.4 in 142 x 483 x 394 mm
Weight	26.0 lb/11.8 kg	39.5 lb/17.9 kg

All specifications subject to change



WARRANTY AND SUPPORT

Visit **WWW.AMPEG.COM** to...

- (1) ...identify **WARRANTY** coverage provided in your local market. Please keep your sales receipt in a safe place.
- (2) ...retrieve a full-version, printable **OWNER'S MANUAL** (English only) for your product.
- (3) ...**REGISTER** your product.
- (4) ...**CONTACT** Technical Support, or call 818-575-3600.

www.ameg.com
Yamaha Guitar Group, Inc.
26580 Agoura Road, Calabasas, CA 91302-1921 USA
Part No. 40-00-0530 Rev. B

