

## Specifications

	KC-550	KC-350	KC-150	KC-60	KCW-1
Rated Power Output	180 W	120 W	65 W	40 W	200W
Nominal Input Level (1 kHz)	CH 1 (MIC/LINE)	-50 to -20 dBu	-50 to -20 dBu	-50 to -20 dBu	-50 to -20 dBu
	CH 2-4 (LINE)	-20 dBu	-20 dBu	-20 dBu	-20 dBu
	STEREO LINK	0 dBu	0 dBu	—	—
	AUX	-10 dBu	-10 dBu	-10 dBu	-10 dBu
Nominal Output Level (1 kHz)	LINE OUT	+4 dBu	+4 dBu	+4 dBu	+4 dBu
	STEREO LINK	0 dBu	0 dBu	—	—
	SUB WOOFER	+4 dBu	+4 dBu	+4 dBu	+4 dBu
Speakers	38 cm (15 inches) x 1, Tweeter x 1	30 cm (12 inches) x 1, Tweeter x 1	30 cm (12 inches) x 1, Tweeter x 1	25 cm (10 inches) x 1, Tweeter x 1	25 cm (10 inches) x 1
Connectors	CH1 INPUT Jack (XLR type) CH1-4 INPUT L (MONO) Jacks (1/4" phone type) CH1-4 INPUT R Jacks (1/4" phone type) LINE OUT L (MONO) Jacks (XLR type, 1/4" phone type) LINE OUT R Jacks (XLR type, 1/4" phone type) AUX IN Jacks (RCA phono type) SUBWOOFER OUT Jack (1/4" phone type) STEREO LINK OUT Jack (1/4" phone type) STEREO LINK IN Jack (1/4" phone type) PHONES Jack (Stereo 1/4" phone type)	CH1 INPUT Jack (XLR type) CH1-4 INPUT L (MONO) Jacks (1/4" phone type) CH1-4 INPUT R Jacks (1/4" phone type) LINE OUT L (MONO) Jack (1/4" phone type) LINE OUT R Jack (1/4" phone type) AUX IN Jacks (RCA phono type) SUBWOOFER OUT Jack (1/4" phone type) STEREO LINK OUT Jack (1/4" phone type) STEREO LINK IN Jack (1/4" phone type) PHONES Jack (Stereo 1/4" phone type)	Channel 1 Input Jacks (XLR type, 1/4" phone type) Channel 2 Input Jack (1/4" phone type) Channel 3 Input Jack (1/4" phone type) Channel 4 Input Jack (1/4" phone type) AUX IN Jacks (RCA phono type) LINE OUT Jack (1/4" phone type) SUB WOOFER OUT Jack (1/4" phone type) PHONES Jack (1/4" TRS phone type, mono signal output)	Channel 1 Input Jacks (XLR type, 1/4" phone type) Channel 2 Input Jack (1/4" phone type) Channel 3 Input Jack (1/4" phone type) AUX IN Jacks (RCA phono type) LINE OUT Jack (1/4" phone type) SUB WOOFER OUT Jack (1/4" phone type) PHONES Jack (1/4" TRS phone type, mono signal output)	INPUT Connectors L, R (XLR type) INPUT Jacks L (MONO), R (1/4" phone type) THRU OUT Connectors L, R (XLR type) THRU OUT Jacks L, R (1/4" phone type) FOOT SW Jack (SUBWOOFER ON/OFF)
Power Supply	AC 117 V, AC 230 V, AC 240 V	AC 117 V, AC 230 V, AC 240 V	AC 117 V, AC 230 V, AC 240 V	AC 117 V, AC 230 V, AC 240 V	AC 117 V, AC 230 V, AC 240 V
Power Consumption	135 W	100 W	55 W	45 W	135 W
Dimensions	590 (W) x 445 (D) x 536 (H) mm, 23-1/4 (W) x 17-9/16 (D) x 21-1/8 (H) inches (excluding casters)	490 (W) x 385 (D) x 470 (H) mm, 19-5/16 (W) x 15-3/16 (D) x 18-9/16 (H) inches	480 (W) x 295 (D) x 435 (H) mm, 18-15/16 (W) x 11-5/8 (D) x 17-1/8 (H) inches	420 (W) x 300 (D) x 410 (H) mm, 16-9/16 (W) x 11-13/16 (D) x 16-3/16 (H) inches	438 (W) x 440 (D) x 460 (H) mm, 17-1/4 (W) x 17-3/8 (D) x 18-1/8 (H) inches
Weight	29.0 kg, 63 lbs 15 oz	22.0 kg, 48 lbs 9 oz	14.0 kg, 30 lbs 14 oz	12.5 kg, 27 lbs 9 oz	23.0 kg, 50 lbs 12 oz
Accessories	Owner's Manual, Casters (x4)	Owner's Manual	Owner's Manual	Owner's Manual	Owner's Manual, Power Cord

\* 0 dBu = 0.775 Vrms

# Roland®

# KC Keyboard Amplifier

## Simply the Best



## The Ultimate Amplifier for Keyboards and Organ.

The KC-1000 is our most powerful keyboard amp ever. This 5-channel tower uses DSP technology and a 310-watt/7-speaker system to accurately reproduce the full frequency range of organs, synthesizers and other electronic musical instruments. Onboard RSS® and COSM® effects create realistic tone cabinet reverberation when used with VK-Series organs, while unique ambient effects, split-frequency compression and 3-band EQ make the KC-1000 perfect for performance.

### Specifications

- **Rated Power Output** 310W ● **Speakers** 15" (38 cm) x 1, 6.3" (16 cm) x 4, 1" (2.5 cm) x 2
- **Controls** Channel Organ Volume, Cabinet Modeling Sound Type, Orchestral Volume, Synth/AUX Volume, Mic Volume, Ambience Volume, Tone Control Low, Tone Control Middle, Tone Control High, Master Volume, Line Out Volume, Phones Volume
- **Connectors** ORGAN Input (L/Mono, R), ORCHESTRAL Input (L/Mono, R), SYNTH/AUX Input (L/Mono, R), MIC Input (Mono), STEREO LINK OUT, STEREO LINK IN, LINE OUT (XLR type balanced L, R, 1/4" phone type unbalanced L/Mono, R), HEADPHONES
- **Power Consumption** 225W (AC 117/230/240 V)
- **Dimensions** (incl. the casters) 595 (W) x 535 (D) x 970 (H) mm (23-7/16" x 21-1/16" x 38-3/16")
- **Weight** 64 kg (141 lbs. 2 oz.)



**KC-1000**  
Stereo Mixing Keyboard Amplifier

## Options



**DR-20**  
Dynamic microphone



**RH-50**  
Headphones



**DP-2**  
Pedal Switch



**FS-5U**  
Footswitch

**Roland®**  
WE DESIGN THE FUTURE

Visit us online at [www.roland.co.jp](http://www.roland.co.jp)

All specifications and appearances are subject to change.  
All trademarks are the property of their respective companies.

Printed in Japan September 2002 RAM-3612 ERK-NK ADE-2