



Rated Power Output

45 W + 45 W

Nominal Input Level (1 kHz)

GUITAR Channel: -10 dBu

MIC/LINE Channel: -50 / -10 dBu

AUX IN: -10 dBu

Nominal Output Level (1 kHz)

DI/TUNER OUT: +4 dBu

LINE OUT: +4 dBu

SUB WOOFER OUT: +4 dBu

Speakers

Woofers: 20cm (8inches) x 2

Tweeters: 8cm x 5cm (3inches x 2inches) x 2

Controls

[GUITAR Channel]

PICKUP Switch (PIEZO, MAGNETIC)

SHAPE Switch

VOLUME Knob

BASS Knob

MIDDLE Knob

TREBLE Knob

CHORUS Switch

[MIC/LINE Channel]

PHANTOM Switch
SELECT Switch (MIC, LINE)
VOLUME Knob
BASS Knob
MIDDLE Knob
TREBLE Knob
CHORUS Switch
[CHORUS]
CHORUS Knob (SPACE, RICH, WIDE)
[REVERB/DELAY]
REVERB/DELAY Knob
[ANTI-FEEDBACK]
FREQUENCY Knob
START Button
MUTE Switch
MASTER Knob
POWER Switch
Indicator
[GUITAR Channel]
CHORUS
[MIC/LINE Channel]
CHORUS
ANTI-FEEDBACK
MUTE
POWER
Connectors
[GUITAR Channel]
Input Jack (1/4-inch phone type)
[MIC/LINE Channel]
Input Jacks
(XLR type, balanced, phantom power : DC 48 V, 10 mA Max)
(1/4-inch TRS phone type, balanced)
AUX IN Jacks
L, R (RCA phono type)
L (MONO), R (1/4-inch phone type)
DI/TUNER OUT Jack (1/4-inch TRS phone type)
LINE OUT Jacks
L, R (XLR type)
MONO (1/4-inch phone type)

SUB WOOFER OUT Jack (1/4-inch phone type)

PHONES Jack (Stereo 1/4-inch phone type)

FOOT SW Jacks

TIP: MUTE, RING: ANTI-FEEDBACK (1/4-inch TRS phone type)

TIP: CHORUS, RING: REVERB/DELAY (1/4-inch TRS phone type)

Power Supply

AC 117 V, AC 230 V, AC 240 V (50/60 Hz)

Power Consumption

30 W

Accessory

Carrying Case

Owner's Manual

Options

Foot Switch: BOSS FS-5L (Mute On/Off), BOSS FS-5U, Dual Footswitch: BOSS FS-6, BOSS FS-7

SIZE AND WEIGHT

Width

464 mm

18-5/16 inches

Depth

303 mm

11-15/16 inches

Height

326 mm

12-7/8 inches

Weight

13.9 kg

30 lbs. 11 oz.