

Features

- 1900 Watt Peak, 950 Watt RMS tri-amplification
- 134 dB max spl
- 80 x 60, Wide dispersion constant directivity horn
- 2x12" woofer, high power neodymium 3" v.c.
- 8" midrange, high power neodymium 3" v.c.
- 1" HF driver, titanium dome, neodymium 1.75" v.c.

Specifications

- Frequency Response -3 dB: 50 Hz ÷ 20000 Hz
- Max SPL: 134 dB
- Horizontal coverage angle: 80°
- Vertical coverage angle: 60°
- Compression Driver: 1" neo, 1.75" voice coil
- Midrange: 8" neo, 3" voice coil
- Woofer: 2 x 12" neo, 3" voice coil
- Input signal: bal / unbal
- Input connectors: Combo xlr-jck
- Output connectors: xlr
- Input sensitivity: 0 dBu
- Crossover frequencies: 360 Hz / 2000 Hz
- Protections: uC protection
- Limiter: Fast limiter
- Controls: Volume
- Total power: 1900 W PEAK
 - High frequencies: 100 W PEAK
 - Mid frequencies: 600 W PEAK
 - Low frequencies: 1200 W PEAK
- Total power: 950 W RMS
 - High frequencies: 50 W RMS
 - Mid frequencies: 300 W RMS
 - Low frequencies: 600 W RMS
- Cooling: Forced
- Connections: Powercon in / out
- Cabinet Material: Baltic birch
- Hardware: 5 x fly tracks
- Handles: 2 side, 1 top
- Colour: Black
- Height: 920 / 36.22 mm/inch
- Width: 525 / 20.67 mm/inch
- Depth: 550 / 21.65 mm/inch
- Net Weight: 55 / 121.25 kg/lbs