



INDUSTRY-LEADING WARRANTY

Crown offers a five-year, no-fault, fully transferable warranty on every new I-Tech HD amplifier we make – an unsurpassed industry standard. With this industry-leading no-fault protection, your I-Tech HD is warranted to meet or exceed original specifications for the first five years of ownership. If it doesn't, it will be repaired or replaced at our expense. That's what being a leader is all about. For warranty information outside of the U.S., contact the Crown authorized distributor in your country. To see full warranty details, visit www.crownaudio.com.

SPECIFICATIONS

CHANNELS	4 inputs routable to any of the 4 outputs (Analog, AES3, VDrive, or CobraNet™)	
SENSITIVITY	Adjustable in 0.1dB increments from 1.28Vrms to 8Vrms	
RATED POWER OUTPUT <small>(minimum guaranteed power in watts with 0.35% THD, all channels driven)</small>	20Hz - 20kHz	1 kHz 20ms Burst
	2Ω	3500W 20ms Burst
	2.7Ω	3800W 20ms Burst
	4Ω	4000W 20ms Burst
	8Ω	2100W 20ms Burst
	70Vrms Direct 100Vrms Direct	2100W 2300W
SIGNAL-TO-NOISE RATIO <small>(below rated power 20Hz to 20kHz A-weighted)</small>	> -108dB	
TOTAL HARMONIC DISTORTION (THD) <small>(full rated power, 20Hz to 20kHz)</small>	0.35%	
INTERMODULATION DISTORTION <small>(from 0dB down to -40dB)</small>	0.06%	
FREQUENCY RESPONSE <small>(20Hz to 20kHz at 1W into 4/8Ω)</small>	+/- 0.25dB	
CROSSTALK <small>(below rated power 20Hz to 1kHz)</small>	> 80dB	
COMMON MODE REJECTION <small>(20Hz to 1kHz)</small>	> 80dB Typical	
DIMENSION <small>(H x W x D)</small>	3.3" x 19" x 16.95"	
	8.9 cm x 48.3 cm x 43.1 cm	
NET WEIGHT	29 lbs (13.2 kgs)	
NET SHIPPING WEIGHT	36 lbs (16.3 kgs)	

DRIVECORE™

OMNIDRIVE HD™
PROCESSING

MICROnet™
performance
manager™

LevelMAX™