

## TECHNICAL SPECIFICATIONS

<b>Acoustical specifications</b>	Frequency Response:	45 Hz ÷ 20000 Hz
	Max SPL @ 1m:	128 dB
	Horizontal coverage angle:	120°
	Vertical coverage angle:	30°
<b>Transducers</b>	Fullrange:	8 x 2.0", 1.0" v.c
	Woofers:	12", 2.5" v.c
<b>Input/Output section</b>	Input signal:	bal/unbal
	Input connectors:	XLR, Jack
	Output connectors:	XLR
	Input sensitivity:	-2 dBu/+4 dBu
<b>Processor section</b>	Crossover Frequencies:	220 Hz
	Protections:	Thermal, RMS
	Limiter:	Soft Limiter
	Controls:	Volume, EQ, phase, Xover
<b>Power section</b>	Total Power:	1400 W Peak, 700 W RMS
	High frequencies:	400 W Peak, 200 W RMS
	Low frequencies:	1000 W Peak, 500 W RMS
	Cooling:	Convection
	Connections:	VDE
<b>Standard compliance</b>	CE marking:	Yes
<b>Physical specifications</b>	Cabinet/Case Material:	Baltic birch plywood
	Hardware:	2 x M6
	Handles:	1 Top
	Pole mount/Cap:	Yes
	Color:	Black
<b>Size</b>	Height:	530 mm / 20.87 inches
	Width:	346 mm / 13.62 inches
	Depth:	459 mm / 18.07 inches
	Weight:	23.8 kg / 52.47 lbs
<b>Shipping informations</b>	Package Height:	580 mm / 22.83 inches
	Package Width:	400 mm / 15.75 inches
	Package Depth:	570 mm / 22.44 inches
	Package Weight:	27.7 kg / 61.07 lbs



**PART NUMBER**

- **13000443**

EVOX 8

115V, Black

EAN 8024530012373

- **13000442**

EVOX 8

220-240V, Black

EAN 8024530012151